



Parameters of Hydraulic Guillotine Shearing Machine

Specification	QC11Y-6X2500	QC11Y-6X3200	QC11Y-6X4000	QC11Y-6X5000	QC11Y-6X6000	QC11Y-8X2500	QC11Y-8X3200	QC11Y-8X4000	QC11Y-8X6000	QC11Y-10X2500
Max Shearing Thickness(mm)	6	6	6	6	6	8	8	8	8	10
Max Shearing Width(mm)	2500	3200	4000	5000	6000	2500	3200	4000	6000	2500
Distance Between Uprights(mm)	2730	3430	4220	5260	6380	2730	3440	4230	6230	2720
Strokes(n/min)	17	14	10	7	6	14	10	8	6	10
Back gauge Stroke(mm)	20-600	20-600	20-600	20-600	20-600	20-600	20-600	20-600	20-600	20-600
Shearing Angle(°)	0.5-1.5°	0.5-1.5°	0.5-1.5°	0.5-2°	0.5-2°	0.5-1.5°	0.5-2°	0.5-2°	0.5-2°	0.5-1.5°
Working Table Height(mm)	780	790	790	936	936	790	836	900	850	800
Throat Depth(mm)	100	100	100	100	100	100	100	100	100	100
Main Power(KW)	7.5	7.5	7.5	7.5	11	11	11	11	11	11
Length(mm)	3100	3800	4650	5800	6800	3150	3850	4700	6900	3100
Width(mm)	1450	1550	1600	2150	2150	1600	1750	1800	1950	1750
Height(mm)	1950	2000	2000	2300	2300	2000	2000	2200	2500	2000
Weight(kg)	4820	6800	7700	14000	17000	6800	7500	8500	19000	7500

QC11Y-10X3200	QC11Y-10X4000	QC11Y-12X2500	QC11Y-12X3200	QC11Y-12X4000	QC11Y-12X6000	QC11Y-16X2500	QC11Y-16X3200	QC11Y-16X4000	QC11Y-20X2500	QC11Y-20X3200	QC11Y-20X4000	QC11Y-25X2500	QC11Y-25X3200	QC11Y-30X2500	QC11Y-30X3200
10	10	12	12	12	12	16	16	16	20	20	20	25	25	30	30
3200	4000	2500	3200	4000	6000	2500	3200	4000	2500	3200	4000	2500	3200	2500	3200
3440	4230	2760	3430	4230	6370	2730	3530	4330	2830	3530	4355	2830	3530	2830	3580
10	12	10	10	7	5	8	7	6	6	5	5	5	5	4	4
20-600	20-600	20-800	20-800	20-800	20-800	20-800	20-800	20-800	20-800	20-800	20-800	20-800	20-800	20-1000	20-1000
0.5-2°	0.5-2°	0.5-2°	0.5-2°	0.5-2°	0.5-2°	0.5-2°	0.5-2°	0.5-2.5°	0.5-2.5°	0.5-3°	0.5-3°	0.5-3°	0.5-3°	0.5-3°	0.5-3°
836	900	830	830	930	1080	860	970	970	920	990	1015	1000	1000	1010	1050
100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100
11	11	15	22	22	22	22	22	22	30	30	30	37	37	45	45
3850	4700	3150	3900	4800	6900	3200	4100	5000	3400	4050	4900	3450	4160	3500	4350
1750	1800	2050	2000	2100	2350	2150	2300	2300	2200	2200	2300	2300	2300	2600	2450
2000	2200	2200	2300	2500	2800	2400	2600	2600	2700	2650	2800	2350	2900	2850	3000
8000	11000	8500	10600	12700	28500	11000	13200	15000	13200	17000	23000	18500	21000	17800	29000

Contact Us

Name: Nantong Liwang Machine Tool Co., Ltd.

Add: Libao Town, Haian County, Nantong, Jiangsu, China

Post Code: 226631

Tel: 0513-88283334

Fax: 0513-88281298

E-mail: wang@ntlwj.cn